Clarion Co., Ltd.

Printed in Japan

PE-9902E

280-6413-00

Clarion ARX9170R

RDS-EON FM-MPX/MW/LW RADIO CASSETTE COMBINATION WITH CD CHANGER CONTROL

COMBINE RADIO-CASSETTE RDS - EON FM-MPX/PO/GO AVEC CONTROLEUR DE CHANGEUR DE CD

RDS-EON UKW-MPX/MW/LW-RADIO-KASSETTEN KOMBINATION MIT CD-WECHSLER-STEUERUNG

Owner's Guide
Manuel de l'utilisateur
Bedienungsanleitung

R·D·S EON

English

1. FEATURES 1
2. CASSETTE PRECAUTIONS AND CARE 4
3. SLOPING PANEL 4
4. D.C.P.(Detachable Control Panel) 5
5. OPERATION 6
6. TROUBLESHOOTING 23
7. ERROR DISPLAYS 24
8. SPECIFICATIONS 25

Français

1. CARACTERISTIQUES 2
2. PRECAUTIONS AVEC LES CASSETTES ET ENTRETIEN . 26
3. PANNEAU OUVRABLE 27
4. D.C.P. (clavier de commande amovible) 27
5. FONCTIONNEMENT 28
6. DEPISTAGE DES PANNES 45
7. AFFICHAGES D'ERREUR 46
8. SPECIFICATIONS 47

Deutsch

1. LEISTUNGSMERKMALE 3
2. KASSETTEN: VORSICHTSMASSNAHMEN UND PFLEGE . 48
3. SCHIEBEBLENDE 48
4. ABNEHMBARES BEDIENTEIL 49
5. BEDIENUNG 50
6. FEHLERSUCHE 67
7. FEHLERDISPLAYS 68
8. TECHNISCHE DATEN 69

Italiano

2. PRECAUZIONI E CURA DELLE CASSETTE 70
3. PANELLO SCORREVOLE 70
4. FRONTALINO ESTRAIBILE (DCP) 71
5. FUNZIONAMENTO 72
6. LOCALIZZAZIONE DEI GUASTI 89
7. DISPLAY DI ERRORE 90

Nederlands

2. VOORZORGSMAATREGELEN BIJ HET BEHANDELEN VAN DE CASSETTE ... 91
3. SCHUIFPANEEL 91
4. DCP (AFNEEMBAAR BEDIENINGSPANEEL) 92
5. BEDIENING 93
6. IN GEVAL VAN PROBLEMEN 110
7. FOUTMELDINGEN 111

Español

2. PRECAUCIONES Y CUIDADOS A TENER CON LOS CASSETTES 112
3. PANEL DESLIZANTE 112
4. DCP (PANEL DE CONTROL DESMONTABLE) ... 113
5. OPERACION 114
6. ANTES DE SOLICITAR REPARACIONES 131
7. INDICACIONES DE ERROR 132

Svenska

2. RÄTT SKÖTSEL AV DINA KASSETTER 133
3. ÖPPNINGSBAR FRONTPANEL 134
4. LÖSTAGBAR FRONTPANEL 134
5. MANÖVRERING 135
6. FELSÖKNING 152
7. FELMEDDELANDEN 153

Português

2. PRECAUÇÕES E CUIDADOS COM AS CASSETES .. 154
3. PAINEL DESLIZANTE 154
4. DCP (PAINEL DE CONTROLO DESTACAVEL) ... 155
5. FUNCIONAMENTO 156
6. RESOLUÇÃO DE PROBLEMAS 173
7. MENSAGENS DE ERRO 174





Operation Angle: 30° in all directions
Angle d'utilisation: 30° dans toutes les directions
Einbauwinkel: 30° in allen Richtungen



Français

1. CARACTERISTIQUES

Tuner

Récepteur EON-RDS avec fonctions PI, PS, AF, TA, PTY, REG, CT et M/S
Syntonisation électronique PLL verrouillée par quartz
Syntonisation automatique/préréglée/manuelle
24 stations mémorisables (18 FM, 6 PO/GO)
Balayage préréglé (PS)
Mémorisation automatique (AS)
Moniteur radio
Commutateur DX/LO

Cassette

Commandes entièrement logiques
Nettoyage automatique de la cassette
Inversion automatique avec ajustement bidirectionnel de l'azimut
Sélecteur automatique de bande métal
Dégagement du galet presseur à la mise hors tension
Commande automatique des programmes (APC)
Saut des intervalles vierges
Répétition
Balayage des sélections musicales
Réduction de bruit Dolby B/C
Tête en permalloy dur à entre-fer double
Mécanisme de transport de bande à sûreté intégrée

Contrôleur de changeur de CD

Commande multi-magasin (6/12/18 disques)
Mémoire du titre du disque
Lecture programmable
Lecture/pause
Lecture aléatoire (Un disque unique/le disque entier)
Balayage des introductions (plage/disque)
Répétition (plage/disque)
Recherche de plage par avance rapide/retour rapide (FF/FB)
Recherche audible à 2 vitesses par avance rapide/retour rapide (FF/FB)

Contrôleur de changer de MD

Affichage de titre du disque
Lecture/pause
Lecture aléatoire (Un disque unique/le disque entier)
Balayage des introductions (plage/disque)
Répétition (plage/disque)
Recherche de plage par avance rapide/retour rapide (FF/FB)
Recherche audible à 2 vitesses par avance rapide/retour rapide (FF/FB)

Audio

Commandes électroniques (volume/graves/aiguës/équilibre/fader)
Sourdine audio
Compensation physiologique
Sortie de niveau de ligne RCA plaquée or 4 canaux
Sortie de niveau de ligne RCA plaquée or 2 canaux (sans fondu)

Généralités

Commande des fonctions principales
Commande DSP/EQ
Grand affichage matricielle à points cachant l'ouverture de cassette
Eclairage de nuit
Couleur d'éclairage des touches: ambre/vert
Heure d'horloge RDS (CT)
Activateur d'antenne électrique
Déclencheur de mise sous tension de l'ampli
Connecteur ISO
Sourdine audio déclenchée pour un téléphone mobile
Télécommande infrarouge

Sécurité

Clavier de commande amovible (avec boîtier de protection)
Indicateur anti-vol clignotant

1. FEATURES

English

Tuner

EON-RDS Receiver with PI, PS, AF, TA, PTY, REG, CT, and M/S
Electronic Quartz-Locked PLL Tuning
Seek/Preset/Manual Tuning
24 Presets (18 FM, 6 MW/LW)
Preset Scan (PS)
Auto Store (AS)
Radio Monitor
DX/LO Switch

Cassette

Full Logic controls
Automatic Tape Head Cleaner
Auto Reverse With Dual Azimuth Adjustment
Automatic Metal Tape Selector
Power-off Pinch Roller Release
Automatic Programme Control (APC)
Blank Skip
Repeat
Intro Scan
Dolby B/C Noise Reduction
Double-Gutter Hard Permalloy Tape Head
Fail-Safe Tape Mechanism

CD Changer Control

Multi-Magazine Control (6/12/18 discs)
Disc Title Memory
Programmable Play
Play/Pause
Random Play (Single Disc/Full Disc)
Intro Scan (Track/Disc)
Repeat (Track/Disc)
Track Search FF/FB
2-Speed Audible Search FF/FB

MD Changer Control

Disc Title Display
Play/Pause
Random Play (Single Disc/Full Disc)
Intro Scan (Track/Disc)
Repeat (Track/Disc)
Track Search FF/FB
2-Speed Audible Search FF/FB

Audio

Electronic Controls (Volume/Bass/Treble/ Balance/Fader)
Audio Muting
Loudness
4-Channel Gold-Plated RCA Line Level Output
2-Channel Gold-Plated RCA Line Level Output (non-fading)

General

Primary Function Control
DSP/EQ control
Dot Matrix Large Display concerning Tape Door
Night Illumination
Switchable Button Illumination Colour: Amber/Green
RDS Clock Time (CT)
Power Antenna Activator
Amp Turn-On Trigger
ISO Connector
Triggered Audio Mute For Cellular Telephone
Infrared Remote Control Unit

Security

Detachable Control Panel (with protective case)
Blinking Theft-Preventing Indicator

1. LEISTUNGSMERKMALE

Deutsch

Tuner

EON-RDS-Receiver mit PI-, PS-, AF-, TA-, PTY-, REG-, CT- und M/S-Funktion
Elektronisches Quartz-PLL-Tuning
Sendersuchlauf/Speihern/Manuelle Abstimmung
24 Stationsspeicher (18 UKW, 6 MW/LW)
Voreinstellungen scannen (PS)
Automatische Speicherung (AS)
Radio-Monitor
DX/LO-Schalter

Kassette

Logiksteuerung
Automatischer Kassettenkopfreiniger
Auto-Reverse mit Azimuth-Einstellung für beide Laufrichtungen
Bandsorten-Automatik
Walzenrückstellung bei Unterbrechung der Stromversorgung
Automatische Programmsteuerung (APC)
Vorspulen bei längeren Aufnahmepausen (Blank Skip)
Wiederholung
Anspielautomatik (Intro Scan)
Dolby B/C-Rauschunterdrückung
Hart-Permalloy-Tonkopf mit doppelter Fuge
Störungssicherer Kassettenmechanismus

CD-Wechsler-Steuerung

Multi -Magazin-Steuerung (6/12/18 CD)
CD-Titel-Speicher
Programmierbare Wiedergabe
Wiedergabe/Pause
Wiedergabe in zufälliger Reihenfolge (Einzelne CD/Ganzes Magazin)
Anspielautomatik (Titel/CD)
Wiederholung (Titel/CD)
Titelanwahl vor/zurück
Hörbarer Suchlauf mit 2 Geschwindigkeiten FF/FB (schneller Vorlauf/Rücklauf)

MD-Wechsler-Steuerung

MD-Titel-Anzeige
Wiedergabe/Pause
Wiedergabe in zufälliger Reihenfolge (Einzelne CD/Ganzes Magazin)
Anspielautomatik (Titel/MD)
Wiederholung (Titel/MD)
Titelanwahl vor/zurück
Hörbarer Suchlauf mit 2 Geschwindigkeiten FF/FB (schneller Vorlauf/Rücklauf)

Audio

Elektronische Einstellung für Lautstärke/Tiefen/Höhen/Balance/Fader
Audio-Stummschaltung
Loudness
4-Kanal RCA Ausgang (vergoldete Cinch-Buchsen)
2-Kanal RCA Ausgang (vergoldete Cinch-Buchsen) (ohne Fader-Regelung)

Allgemeine Merkmale

Multifunktions-Taste
DSP/EQ -Taste
Großes Punktmatrix-Display, das die Kassettenöffnung verdeckt.
Nachtbeleuchtung
Umschaltbare Beleuchtungsfarbe: orange/grün
RDS-Uhrzeit (CT)
Anschluß für elektrische Antenne
Anschluß für Verstärker Ein/Aus
ISO-Steckverbinder
Automatische Stummschaltung bei anschluß eines Funk-Telefons
Infrarot-Fernbedienung

Sicherheit

Abnehmbares Bedienteil (mit Schutzhülle)
Blinkende Diebstahlwarnanzeige

2. CASSETTE PRECAUTIONS AND CARE

English

1. Tape slack can lead to operating difficulties. Remove tape slack before inserting a cassette, particularly when using C-90 or prerecorded cassettes.
2. Use C-30 to C-90 cassettes. Avoid use of C-120 or longer cassettes (The very thin tape may stretch or break):
3. Clean the head periodically by playing a wet- type cleaning cassette in the player.
   Avoid touching the head with magnetic or hard objects.
4. Do not oil the cassette mechanism.
5. Always remove the cassette from the mechanism when not in use. Exposure to direct sunlight, extreme temperatures or high humidity may damage cassettes.
6. The cassette is automatically ejected if the unit detects slack or other problems in the tape. Make sure the cassette tape is in order before using it.

3. SLOPING PANEL

1. The sloping panel uses a precision opening/closing mechanism. Do not operate it with excessive force or use it in unusual ways. for safety, keep the sloping panel closed whenever possible when not operating it.
2. Be careful not to let your fingers get caught when opening and closing the sloping panel.
3. The sloping panel may be damaged or deformed if subject to strong impacts.



4. DCP (Detachable Control Panel)

English

The control panel can be detached to prevent theft. When detaching the control panel, store it in the included DCP case to prevent scratches. We recommend taking the control panel with you when leaving the car.

Removing the DCP

1 Turn the power off.
2 Press the release button [1].
  * The DCP is unlocked.
3 Remove the DCP.



Attaching the DCP

Insert the DCP into the right side of the main unit and press the left side to lock it. Do not insert the DCP from the left side. Doing so may damage it.



Storing the DCP in the DCP case

1 Insert the DCP into the right side of the case, and press the left side to lock it.
2 To remove from the case, press the DCP to the right and draw it out upwards.



NOTE:

*Close the sloping panel when removing or attaching the DCP.
*The DCP can easily be damaged by shocks. After removing it, place it in its case and be careful not to drop it or subject it to strong shocks.
* When the release button is pressed and the DCP is unlocked, the car's vibrations may cause it to fall. To prevent damage to the DCP, always store it in its case after detaching it.
* The connector connecting the main unit and the DCP is an extremely important part. Be careful not to damage it by pressing on it with fingernails, pens, screwdrivers, etc.
* If the DCP is dirty, wipe off the dirt with a soft, dry cloth.



ANTI-THEFT INDICATOR

A red indicator can be set to flash as a means of preventing theft. This flashing red indicator warns thieves that the anti-theft device is activated.

1) Press the ADJ button [14].
2) Use the Up and Down buttons (▲ ▼) [15] to select "GENERAL".
3) Press the ENT button [17].
4) Use the Right and Left buttons (◀◀ ▶▶) [16] to select "BLINK LED".
5) Use the Up and Down buttons (▲ ▼) [15] to select "on".
   * If "off" is selected, the indicator is turned off.
6) Press the ADJ button [14] to return to the previous mode.
7) The red indicator flashes when the DCP is removed from the main unit.

5. OPERATION

English

Names of Buttons

1. DCP release button
2. TA/PTY button
3. RPT (repeat) button [📼], [💿], [💽]
   RDS button [📻]
4. EQ (equalizer) button
5. DSP (digital sound processor) button
6. PROGRAM button [📼]
   BAND/T.MODE button [📻]
   MAG (magazine) button [💿]
7. OPEN button [📼]
   Eject (⏏) button [📼]
8. DISP (display) button
   SHIFT button
9. Direct buttons (1 to 6) [📻], [💿], [💽]
10. SCN (scan) button [📼], [💿], [💽]
    PS/AS (preset scan/auto store) button [📻]
11. DOLBY NR button [📼]
    RDM (random) button [💿], [💽]
    DX/LO (DX/local) button [📻]
12. A-M (audio mode) button
    LD (loudness) button
13. POWER button
    FUNC (function) button
14. ADJ (adjust) button
    P.ME (programme memory) button [💿]

Primary Function Control

15. Up and down (▲ and ▼) buttons
16. Left and right (◀◀ and ▶▶) buttons
17. Mute button [📻]
    Play/pause (▶/II) button [📼], [💿], [💽]
    P.PLAY (programme play) button [💿]
    ENT (enter) button

[📻] : In the radio mode
[📼] : In the Tape mode
[💿] : In the CD changer mode
[💽] : In the MD changer mode

Primary Function Control operation

The Primary Function Control is an important aspect of the ARX9170R.
To select ▲, ▼, ◀◀ or ▶▶ : Press one of the four sides of the Primary Function Control.



To use the ▶/II button: Press on the centre of the button.



NOTE:
Do not turn the button while operating any primary function controls.

Adjustments made with the ADJ button

(not including DSP and equalizer adjustments)
The "*" mark indicates initial settings.

Adjustment	Settings	Mode in which adjustment is possible	Page
RDS setting	*on off	Any mode	12
Regional setting	*on off	Any mode as long as the RDS function is on	13
PTY code setting	*NEWS ~ OTHER M		13
Button Illumination	COLOR-1 (G) * COLOR-2 (A)	Any mode	18
BLINK LED setting	*off on		5
Seek tuning sensitivity	*DX LOCAL	Radio mode	11
Volume setting for traffic announcements, etc.	VOL 0 ~ VOL 33		15
AS band	*FM1/2/3 FM3		12
M/S setting	*off on	Radio mode with the RDS function on	13
Blank skip setting	*off on	Tape mode	11
Programme play Programme erase	1~50	CD changer mode	16 16
Title input	Input of up to 11 characters		17
Title clear	1~100		17
Title list display	1~100		17
MD display	*DISC TRACK	MD changer mode	18

English

Functions of Remote Control Unit Buttons

Button \ Mode	Radio	Cassette	CD Changer/MD Changer
18 FUNC	Switches between radio, cassette tape, CD changer and MD changer.		
19 BAND/DISC PROG-TOP	Switches reception band. When pressed for more than 2 seconds: Switches between seek and manual tuning modes.	Switches the side of the tape.	Moves to the next disc in increasing order.
20 VOLUME (▲▼)	Increases and decreases volume (in all modes).		
21 SEARCH (◀◀ ▶▶)	Moves preset channels up and down.	Fast-forwards and rewinds tape. APC fast-forward and rewind.	Moves tracks up and down. When pressed for more than 1 second: Fast-forward/fast-backward.
22 (▶/II) P.PLAY	Turns mute on and off.	Switches between playback and pause.	Switches between playback and pause. When pressed for more than 2 seconds: Starts and stops programme playback (for CDs only).
23 DISPLAY	Switches between main display, character display and time display. When pressed for more than 1 second: Scrolls the titles (for MDs only).		
24 DSP PROGRAM	Moves the DSP programme up.		
25 EQ PROGRAM	Moves the equalizer programme up.		
26 PS/AS SCAN	Preset scan. When pressed for more than 2 seconds: Auto store.	Fast Forward Scan.	Scan. When pressed for more than 2 seconds: Disc scan.
27 DX/LO DOLBY NR RANDOM	Switches between DX and local reception.	Selects Dolby Noise Reduction mode.	Random play. When pressed for more than 2 seconds: Disc random play.
28 RDS REPEAT	Turns RDS on and off.	Repeat play.	Repeat play. When pressed for more than 2 seconds: Disc repeat play.
29 TA/PTY	TA. When pressed for more than 2 seconds: PTY (when RDS is on).		

* Some of the corresponding buttons on the main unit and remote control unit have different functions.
* The ARX9170R is not equipped with the Top function.

Inserting the Battery

1) Turn the remote control unit upside down, push the lock on the bottom in the direction of the arrow, and pull out the lid.
2) Insert the included battery (CR2025) with the "+" side facing up.
3) Push the lid back in securely until a click is heard.



NOTE:

Using batteries improperly can cause them to explode. Heed the following points:

* When replacing the battery, be sure to set the new battery with the "+" side facing up.
* Do not short-circuit, disassemble or heat batteries.
* Do not dispose of batteries in flames.
* Dispose of spent batteries in the proper place.

Basic Operation

CAUTION

Turning the power on and off with the volume set at the maximum position has a negative effect on the unit and could harm your ears. Be careful to set the volume to an appropriate level.

1) Press the POWER button 13.
   * To turn the power off, press the POWER button for at least 1 second.
2) Press the FUNC button 18 to select the operation mode. The mode switches as follows each time the FUNC button is pressed:
   Radio → Tape → CD changer → MD changer → Radio
   * If a component is not connected, that operation mode cannot be selected.
   * "NO CASSETTE" appears when no tape is loaded in the ARX9170R, and "NO DISC" or "NO MAGAZINE" appears when no disc is loaded in the CD changer or MD changer.
3) Use the up and down buttons 15 to adjust the volume.
   ▲ : Increases the volume.
   ▼ : Decreases the volume.

Audio mode adjustments

1) Press the A-M button 12 to select the audio mode. The mode switches as follows each time the A-M button is pressed:
   BASS/TREB → BAL/FAD → Previous mode
2) Use the left and right and the up and down buttons 15 16 to adjust the bass and treble.
   <Adjusting the bass>
   ▶▶ : Bass gets stronger.
   ◀◀ : Bass gets weaker.
   <Adjusting the treble>
   ▲ : Treble gets stronger.
   ▼ : Treble gets weaker.
3) Use the left and right and the up and down buttons 15 16 to adjust the balance and fader.
   <Adjusting the balance>
   ▶▶ : Sound from right speakers gets stronger.
   ◀◀ : Sound from left speakers gets stronger.
   <Adjusting the fader>
   ▲ : Sound from front speakers gets stronger.
   ▼ : Sound from rear speakers gets stronger.

Loudness function

Press the LD button 12 for at least 2 seconds to turn the loudness function on and off.
"LD" appears on the display when the loudness function is on.

* When a DSP unit (DPH9100) is connected, the loudness effect is automatically controlled.

Switching the display

The display changes as follows each time the DISP button 8 is pressed:
Operation mode display → Character display → Time display → Operation mode display

* The character display is displayed during playback on the tape deck, CD changer or MD changer and in the radio mode.

Mode display

Character display

Time display



* These examples are for the radio mode.

English

Tape Operation

Loading tapes

1) When the OPEN button [7] is pressed, the sloping panel opens.
   * The sloping panel closes if a cassette tape is not loaded within 30 seconds.
   * If a cassette tape is already loaded, it is ejected.
2) Insert the cassette tape into the slot with the exposed tape side to the right. Playback starts and the sloping panel closes.



The metal tape setting is set automatically when a metal or chrome tape is loaded.

* When the end of the cassette tape is reached, the auto reverse mechanism is activated and the other side of the tape begins playing automatically.



Listening to a tape which is already loaded
Press the FUNC button [13] to select the tape mode. Playback begins automatically.

* When the ARX9170R is switched to another mode during the tape fast-forward, rewind or search operation, the tape mechanism automatically stops once the operation is completed. (Monitor function)

Stopping playback temporarily

Press the play/pause button [17]. Press the button again to resume playback.

Ejecting cassette tapes

Press the eject button [7]. The sloping panel slides open and the cassette tape is ejected. Press the eject button again to close the sloping panel.

* The sloping panel closes if a cassette tape is not loaded within 30 seconds.
* The unit switches to the radio mode automatically 4 seconds after the eject button is pressed.

Fast-forwarding and rewinding

Use the left and right buttons [16].

▶▶: Press this to fast-forward the tape.

◀◀: Press this to rewind the tape.

APC (Auto Programme Control)

Press the left or right button [16] twice.

▶▶: Press this to move ahead to the beginning of the next track.

◀◀: Press this to move back to the beginning of the current track.

Switching to the other side of the tape

Press the PROG button [6]. Playback is automatically switched to the other side of the cassette tape.

FF scan function

When the SCN button [10] is pressed, "SCN" appears on the display, and the first 10 seconds of all the tracks on the cassette tape are played. Press the SCN button again to stop scanning.

Repeat function

When the RPT button [3] is pressed, "RPT" appears on the display and the current track is played repeatedly. Press the RPT button again to cancel the repeat mode.

Dolby Noise Reduction System

Press the DOLBY NR button [11] to select the Dolby NR mode ("B NR" or "C NR"). The mode switches as follows each time the DOLBY NR button is pressed:

Off → B NR → C NR → Off

* Dolby Noise Reduction is manufactured under license of the Dolby Laboratories Licensing Corporation. "DOLBY" and the double D mark DD are registered trademarks of the Dolby Laboratories Licensing Corporation.

Blank skip function

Use this function to automatically skip to the beginning of the next recorded section when there is a blank section of 12 seconds or more on the tape.

1) In the tape mode, press the ADJ button [14].
2) Use the up and down buttons [15] to select "UTILITY".
3) Press the ENT button [17]. "BLANK SKIP" appears on the display.
4) Use the up and down buttons to select "on". The blank skip function is now set.
   * "BLS" is lit on the display when the blank skip function is on.
   * Select "off" to turn the blank skip function off.
5) Press the ADJ button.

NOTE:
The APC, scan, repeat and blank skip functions will not work with the following types of tapes:

* Tapes on which the recording level is low
* Tapes on which there is less than 4 seconds of blank space between tracks
* Tapes on which there are long pauses in the middle of tracks
* Tapes on which there is much noise between selections

Radio Operations

Listening to the radio

1) Press the FUNC button [13] and select the radio mode. The radio turns on.



2) To tune in a preset station, first press the BAND button [6] and select FM1, FM2, FM3 or AM(LW/MW).
   The band changes as follows each time the BAND button is pressed:
   FM1 → FM2 → FM3 → AM → FM1
3) Use the direct buttons [9] to select the desired station.

Seek tuning

1) Press the BAND button [6] and select the desired band.
2) The seek tuning mode is set when "SRCH" is lit on the display.
3) Use the left or right button [16]. Seek tuning automatically stops when a station is found.
   * There are two seek tuning modes: DX seek, in which all receivable stations are tuned in in order, and local seek, in which only stations with good reception are tuned in.

Switching between DX and local

The DX mode is set when "DX" is lit on the display.

Switching (1)
In the radio mode, press the DX/LO button [11] to switch between "DX" and "LOCAL".

Switching (2)

1) Press the ADJ button [14].
2) Use the up and down buttons [15] to select "UTILITY", then press the ENT button [17].
3) Use the left and right buttons [16] to select "DX/LOCAL".
4) Use the up and down buttons to select "DX" or "LOCAL".
5) Press the ADJ button.

Manual tuning

1) Press the BAND button [6] and select the desired band.
2) Press the BAND button again for more than 2 seconds. "SRCH" turns off and the manual tuning mode is set.
3) Use the left and right buttons [16] to tune in the desired frequency.
   * The mode automatically returns to the seek mode after 7 seconds.

Presetting stations

A total of 24 stations can be preset, 6 each for the FM1, FM2, FM3 and AM bands.

NOTE:
When a station is preset, the station previously stored in the memory at that position is cleared.

Presetting stations manually

1) Press the BAND button [6] to select the band at which to store the station.
2) Use the left and right buttons [16] to tune in the station to be preset.
3) Press the direct button [9] at which you want to store that station for at least 2 seconds.

Auto store function

1) Press the BAND button [6] to select the band at which to store the stations.
2) Press the AS button [10] for more than 2 seconds. Stations with good reception are automatically stored at direct buttons [9] 1 to 6.
   * If there are fewer than 6 stations with good reception, the stations previously stored at the remaining buttons are not cleared.

Setting the band(s) for the auto store function

If there are preset frequencies you do not want to clear, change the band(s) for which the auto store function can be used.

1) Press the ADJ button [14].
2) Use the up and down buttons [15] to select "UTILITY", then press the ENT button [17].
3) Use the right and left buttons [16] to select "AS BAND ADJ".
4) Use the up and down buttons [15] to select "FM1/2/3" or "FM3".
   * When "FM3" is selected, the auto store function can only be used for the FM3 band.
5) Press the ADJ button.

Preset scanning

When the PS button [10] is pressed, the preset memory numbers flash and the stations are tuned in for 7 seconds each in the order in which they were stored. Press the PS button again to cancel the preset scanning mode.

NOTE:

The auto store mode is set if the PS button is pressed for more than 2 seconds.

Mute

Use this function to turn off the sound immediately.

Press the MUTE button [17]. The sound turns off and "MUTE" appears on the display. Press the MUTE button again to cancel the mute mode.

RDS (Radio Data System) Operations

About the RDS functions

* When an RDS station is tuned in, the programme name is displayed. (PS: Programme Service name)
* When an emergency broadcast is received while an RDS station is tuned in, "ALARM" is displayed. The volume is automatically set to the preset volume level.
* If the RDS station can no longer be received in good conditions in the current location, "RDS" flashes on the display. "RDS" stops flashing when good reception is again possible.
* When seek tuning is used while in the RDS mode, only stations broadcasting RDS signals are tuned in.

Preset scanning in the RDS mode

When the PS button [10] is pressed while in the RDS mode, only preset RDS stations are scanned.

Auto store function in the RDS mode

When the AS button [10] is pressed for more than 2 seconds while in the RDS mode, only RDS stations are stored at the preset buttons.

Selecting the RDS mode (1)

Press the RDS button [3]. This turns the RDS mode on and off.

* This is only possible when in the radio mode.
* "RDS" is lit when the RDS mode is on.

Selecting the RDS mode (2)

1) Press the ADJ button [14].
2) Use the up and down buttons [15] to select "GENERAL", then press the ENT button [17].
3) Use the left and right buttons [16] to select "RDS".
4) Use the up and down buttons [15] to select "on".
5) Press the ADJ button.
   * "RDS" is lit when the RDS mode is on.

Switching (over) to the best alternative frequency broadcasting the same programme (AF: Alternative Frequencies)

Whenever a preset button is pressed, the best conditioned RDS station broadcasting the same programme can be tuned in automatically.

Regional programme function (REG)

When this function is on: Only local (regional) stations in the local area are received.
When this function is off: When you enter another area while receiving a regional station in the first area, a regional station in the new area is tuned in.

1) Press the ADJ button [14].
2) Use the up and down buttons [15] to select "GENERAL", then press the ENT button [17].
3) Use the left and right buttons [16] to select "REG".
4) Use the up and down buttons [15] to select "on".
5) Press the ADJ button.
   * This operation is only possible when the RDS mode is on.

Searching for other programmes in the regional mode

When the regional programme mode is off and a preset RDS station is tuned in, another regional station is tuned in when the same preset button is pressed again.

* This function may not work in some regions.

RDS EON (Enhanced Other Networks information)

"EON" lights when an RDS station's EON data is received.

1) When a traffic announcement starts while in the traffic announcement standby mode, "EON" lights and the traffic announcement is automatically tuned in, even when it is on a station other than the one which is currently tuned in.
2) When a programme of the selected programme type starts while in the PTY standby mode, "EON" lights and that programme is automatically tuned in, even when it is on a station other than the one which is currently tuned in.
   * Some countries and stations do not transmit EON data.

Music/Speech function (M/S)

This function automatically turns the loudness function off so that dialogues are easier to hear.

1) Press the ADJ button [14].
2) Use the up and down buttons [15] to select "UTILITY", then press the ENT button [17].
3) Use the left and right buttons [16] to select "M/S ACT".
4) Use the up and down buttons to select "on".
5) Press the ADJ button.
   * The music/speech function will not work when the DPH9100 or DPH7100 is connected.
   * The music/speech function can only be turned on and off when in the radio mode with the RDS mode on.
   * Some stations do not broadcast the data for turning the loudness function off.

PTY (Programme Type) function

This function uses RDS PTY data so that stations broadcasting programmes of the desired programme type (PTY) can be tuned in using one of the following two methods:

(1) PTY SEEK: Use this to immediately turn on PTY SEEK for stations broadcasting programmes of the selected programme type.
(2) PTY standby: Use this to automatically interrupt the current operation and tune in stations broadcasting programmes of the select-

ed programme type, using the EON data.

* The PTY function does not work unless the RDS mode is turned on. "RDS" is lit on the display when the RDS mode is on.
* When in the traffic announcement standby mode, traffic announcements have priority over PTY broadcasts.
* Some countries and stations do not transmit PTY and EON data.

Selecting the PTY SEEK mode

1) Press the ADJ button [14].
2) Use the up and down buttons [15] to select "GENERAL", then press the ENT button [17].
3) Use the left and right buttons [16] to select "PTY SEL".
4) Use the up and down buttons to select one of the PTY codes, from "NEWS" to "OTHER M".
5) Press the ENT button [17]. "PTY" appears on the display, the PTY SEEK operation begins, and when a station is found, the selected PTY is displayed.
   * If there are no stations broadcasting programmes of the selected programme type, the previous station is tuned in and the PTY standby mode is set automatically.

Selecting the PTY standby mode (1)

1) Press the ADJ button [14].
2) Use the up and down buttons [15] to select "GENERAL", then press the ENT button [17].
3) Use the left and right buttons [16] to select "PTY SEL".
4) Use the up and down buttons to select one of the PTY codes, from "NEWS" to "OTHER M".
5) Press the ADJ button to return to the previous mode. "PTY" lights and the PTY standby mode is set.

Selecting the PTY standby mode (2)

Follow steps 1) to 3) in "Selecting the PTY standby mode (1)" to select "PTY SEL", then press one of the direct buttons [9]. The PTY standby mode for the programme type stored at that button is set.

Presetting programme types

Follow steps 1) to 4) in "Selecting the PTY standby mode (1)" to select the programme type, then press one of the direct buttons [9] for more than 2 seconds. That programme type is stored in the memory, and "P1 MEMO" appears on the display (when direct button "1" is pressed).

* Six programme types can be stored, one each at buttons 1 to 6.

Canceling the PTY standby mode

To cancel the PTY standby mode, press the PTY button [2] for more than 2 seconds. "PTY" turns off. To set the PTY standby mode again, press the PTY button again for more than 2 seconds.

* When the PTY button is pressed while receiving a programme of the selected programme type, PTY reception is canceled and the PTY standby mode is set.

PTY display function

Use this function to display the programme type of the station currently tuned. Press the DISP button [8] to switch the display.

* "– – – – –" is displayed if the PTY data cannot be received.

TA (Traffic Announcement) function

This function automatically tunes in traffic announcements when they start.

Press the TA button [2]. "TA" lights and the radio starts searching for stations broadcasting traffic announcements.

To turn the TA function off, press the TA button again. However, when the TA button is pressed while a traffic announcement is tuned in, the traffic announcement mode is cancelled and the TA stand by mode is set.

* The traffic announcement standby mode is set when there is (are) a station(s) broadcasting traffic announcements.
* When a traffic announcement has started, "TRA INFO" is displayed, after which the PS (Programme Service name) or the frequency appears.
* When a traffic announcement starts, the loudness function is turned off and the volume is automatically set to the preset level.
* When the TA button is pressed while tuned in to a station which is not broadcasting traffic announcements, the radio searches for a station which is broadcasting traffic announcements.
* If no traffic announcement is found, "NO TRA" is displayed. Press the TA button to cancel the TA mode.

Preset scanning when "TA" is lit or flashing

When the PS button [10] is pressed while "TA" is lit or flashing, only preset traffic announcement stations are scanned.

Auto store when "TA" is lit or flashing

When the AS button [10] is pressed for more than 2 seconds while "TA" is lit or flashing, only preset traffic announcement stations are stored.

Setting the volume for traffic announcements and emergency broadcasts

1) Press the ADJ button [14].
2) Use the up and down buttons [15] to select "UTILITY", then press the ENT button [17].
3) Use the left and right buttons [16] to select "TA VOL ADJ".
4) Use the up and down buttons to adjust the volume.
5) Press the ADJ button.

* This operation is only possible in the radio mode.

Time display function (CT: Clock Time)

The time can be displayed in areas broadcasting CT data.

Press the DISP button [8] to switch the display.

* Some countries and stations do not broadcast CT data. Also note that in some areas the displayed time may be wrong.
* "CT– – : – –" is displayed when no CT data is being received.

CD Changer Operations

When a separately sold CD changer (CDC605/CDC1205/CDC1805) is connected, it can be controlled from the ARX9170R.

CD-ROMs

* CD-ROMs cannot be played.

Listening to CDs

1) Press the FUNC button [13] to select the CD changer mode. Playback starts automatically.
   * The pause mode is set when the CD changer mode is set after the power is turned on or while the magazine is being loaded in the CD changer. In these cases, press the play/pause button [17] to start playback.



2) Press the play/pause button [17] to stop playback temporarily.
3) Use the direct buttons [9] to select the desired disc.
   * Nothing happens if a direct button corresponding to the number of a magazine in which no disc is loaded is pressed.
   * When a disc which is currently playing is selected, playback resumes from the first track on that disc.
4) Use the left and right buttons [16] to select tracks.
   ▶▶ : Press this to start playback from the beginning of the next track.
   ◀◀ : Press this to move back to the beginning of the current track. Press it again to move back to the beginning of the previous track.
   * Titles can be given to discs and displayed. If no title has been given, "– – – – –" is displayed.

Fast forward and fast backward

Press and hold in the left and right buttons [16].

▶▶ : Press and hold this to move rapidly forward.

◀◀ : Press and hold this to move rapidly backward.

* The disc moves at 3 times the normal speed after the button is held in 1 second, at 30 times the normal speed after it is held in 3 seconds.

Scan function

When the SCN button [10] is pressed, "SCN" appears on the display, and the first 10 seconds of all the tracks on the disc are played. Press the SCN button again to stop scanning.

Disc scan function
When the SCN button⑩ is pressed for more than 2 seconds, "DISC" and "SCN" appear and the first 10 seconds of the first track on all the discs are played. Press the SCN button again to stop scanning.

Repeat function

When the RPT button③ is pressed, "RPT" appears on the display and the current track is played repeatedly. Press the RPT button again to cancel the repeat mode.

Disc repeat function
When the RPT button③ is pressed for more than 2 seconds, "DISC" and "RPT" appear on the display and the current disc is played repeatedly. Press the RPT button again to cancel the disc repeat mode.

Random playback

When the RDM button⑪ is pressed, "RDM" appears on the display, and all the tracks on the disc are played in random order. Press the RDM button again to cancel the random play mode.

Disc random playback
When the RDM button⑪ is pressed for more than 2 seconds, "DISC" and "RDM" appear on the display, and all the tracks on all the discs in the CD changer are played in random order. Press the RDM button again to cancel the disc random play mode.

Programmed playback

Up to 50 tracks can be programmed to play repeatedly in the programmed order.

Programming tracks
1) Select the track to be set in the programme list and start playing it.
2) Press the P.ME button⑭ for at least 2 seconds. The number of the currently playing track is stored in the programme memory.
3) Repeat steps 1) and 2) to make the programme list.

Playing the programmed tracks
Press the P.PLAY button⑰ for more than 2 seconds. The tracks are played in the programmed order.

To resume normal playback, press the P.PLAY button again for more than 2 seconds.

* "NO PROGRAM" appears if no tracks have been stored in the programme memory.
* If a disc containing a programmed track has been removed, that track is skipped.

Playing from programme lists
It is also possible to start playback from the middle of a programme list.
1) In the CD changer mode, press the ADJ button⑭.
2) Use the up and down buttons⑮ to select "P.PLAY".
3) Press the ENT button⑰. "P.PLAY LIST" appears, and the display switches to the programme list.
4) Use the up and down buttons to select the track you want to hear.
5) Press the ENT button for more than 2 seconds. Playback starts from the selected track.

Clearing tracks from the list
1) In the CD changer mode, press the ADJ button⑭.
2) Use the up and down buttons⑮ to select "P.PLAY", then press the ENT button⑰.
3) Use the left and right buttons⑯ to select "P.PLAY CLR".
4) Use the up and down buttons⑮ to select the track to be cleared.
5) Press the ENT button for more than 2 seconds. The selected track is cleared.
6) Press the ADJ button.

Switching the magazine (When the CDC1205 or CDC1805 is connected)

This function can be used when a CD changer with multiple magazines is connected.
The next magazine is selected each time the MAG button⑥ is pressed.

Locking the magazine
Press the MAG button⑥ for more than 2 seconds. "[CD]" appears on the display, and only the currently displayed magazine is played.
To cancel this, press the MAG button again for more than 2 seconds.

* Magazines can be selected even when a magazine is locked. When this is done, the selected magazine is locked.
* When a magazine is locked, scanning and random playback are only performed for the locked magazine.

Giving titles

Titles can be given to discs and displayed. Up to 100 titles can be stored in the memory.
1) Select the disc to which you want to give a title.
2) Press the ADJ button⑭.
3) Use the up and down buttons⑮ to select "TITLE".
4) Press the ENT button⑰. "TITLE INPUT" appears on the display, and the display switches to the title input display.
5) Use the left and right buttons⑯ to set the cursor position.
   * Up to 11 characters can be set.
6) Use the up and down buttons⑮ to select the letters or numbers.
   * When the DISP button is pressed, the characters change as follows:
   Capital letters → Numbers → Umlauts and accented letters → Small letters → Symbols → Capital letters
7) Repeat steps 5) and 6) to input the title.
8) Press the ENT button for more than 2 seconds. The title is stored in the memory.
9) Press the ADJ button.

Calling out a list of titles
1) Set the CD changer mode.
2) Press the ADJ button⑭.
3) Use the up and down buttons⑮ to select "INDEX".
4) Press the ENT button⑰. "TITLE LIST" appears on the display, and the display switches to the title list display.
5) Use the up and down buttons to select the title.
6) If the ENT button is pressed for more than 2 seconds while the title is displayed, playback begins from the disc with the selected title.

Clearing titles from the title list
1) Set the CD changer mode.
2) Press the ADJ button⑭.
3) Use the up and down buttons⑮ to select "INDEX", then press the ENT button⑰.
4) Use the left and right buttons⑯ to select "TITLE CLR". The display switches to the title list display.
5) Use the up and down buttons to select the title to be cleared.
6) Press the ENT button for more than 2 seconds to clear the selected title.
7) Press the ADJ button.

MD Changer Operations

When a separately sold Mini Disc changer (MDJ474) is connected, it can be controlled from the ARX9170R.

Listening to MDs

1) Press the FUNC button⑬ to select the MD changer mode. Playback starts automatically.



When the MD changer mode is set, the disc title is displayed. "- - - - -" is displayed if no title has been input. Also, when the SHIFT button⑧ is pressed, the display switches between the track number play time, title and clock.
2) Press the play/pause button⑰ to stop playback temporarily.
3) Use the direct buttons⑨ to select the desired MD.
   * Nothing happens if a direct button at which no MD is loaded is pressed.
   * When the MD which is currently playing is selected, playback resumes from the first track on that MD.
4) Use the left and right buttons⑯ to select tracks.
   ▶▶ : Press this to start playback from the beginning of the next track.
   ◀◀ : Press this to move back to the beginning of the current track. Press it again to move back to the beginning of the previous track.

Fast forward and fast backward

Press and hold in the left and right buttons [16].

▶▶ : Press and hold this to move rapidly forward.

◀◀ : Press and hold this to move rapidly backward.

* The disc moves at 3 times the normal speed after the button is held in 1 second, at 15 times the normal speed after it is held in 3 seconds.

Scan function

When the SCN button [10] is pressed, "SCN" appears on the display, and the first 10 seconds of all the tracks on the MD are played. Press the SCN button again to stop scanning.

* Scanning starts from the track following the one that is currently playing.

Disc scan function

When the SCN button [10] is pressed for more than 2 seconds, "DISC" and "SCN" appear and the first 10 seconds of the first track of all the MDs are played.Press the SCN button again to stop scanning.

* Scanning starts from the MD following the one that is currently playing.

Repeat function

When the RPT button [3] is pressed, "RPT" appears on the display and the current track is played repeatedly. Press the RPT button again to cancel the repeat mode.

Disc repeat function

When the RPT button [3] is pressed for more than 2 seconds, "DISC" and "RPT" appear on the display and the current MD is played repeatedly. Press the RPT button again to cancel the disc repeat mode.

Random playback

When the RDM button [11] is pressed, "RDM" appears on the display, and all the tracks on the current MD are played in random order. Press the RDM button again to cancel the random play mode.

Disc random playback

When the RDM button [11] is pressed for more than 2 seconds, "DISC" and "RDM" appear on the display, and all the tracks on all the MDs in the MD changer are played in random order.

Press the RDM button again to cancel the disc random play mode.

Scrolling titles

Press the SHIFT button [8] for more than 1 second while in the title display mode to scroll the titles.

Selecting titles

1) Press the ADJ button [14].
2) Use the up and down buttons [15] to select "UTILITY".
3) Press the ENT button [17]. "D/T TITLE" is displayed.
4) Use the up and down buttons [15] to select "DISC" or "TRACK".
5) Press the ADJ button.

Other Handy Functions

Switching the colour of the button illumination

The colour of the buttons can be switched between green and amber.

1) Press the ADJ button [14].
2) Use the up and down buttons [15] to select "GENERAL", then press the ENT button [17].
3) Use the left and right buttons [16] to select "ILLUM".
4) Use the up and down buttons [15] to select "COLOR-1" or "COLOR-2".
   * The illumination turns green when "COLOR-1" is selected, amber when "COLOR-2" is selected.
5) Press the ADJ button.

Triggered audio mute for cellular telephones

With this function, "TELEPHONE" appears on the display and the sound is muted when a call is received. The previous operation resumes when the line is disconnected.

DSP and Equalizer Operations

When a separately sold expanded graphic digital sound processor or expanded graphic equalizer is connected, the functions described below can be controlled from the ARX9170R.

Fine-adjustment of the listening position (when the DPH9100 or DPH7100 is connected)

The time required from when the sound leaves the speaker until it reaches you can be fine - adjusted to create a natural sound field, no matter what seat you are sitting in.

Numerous preset sound fields (when the DPH9100 or DPH7100 is connected)

The most common sound fields are already stored in the memory.
In addition, six other sound field settings adjusted by the user can also be stored in the memory (when the DPH9100 is connected).

Six preset equalizer settings (when the DPH9100, DPH7100, or EQH5100 is connected)

Six equalizer settings are preset, offering a choice of the settings for various types of music. In addition, six other settings adjusted by the user can also be stored in the memory.

Giving titles (only when the DPH9100 is connected)

Titles can be given to the user-adjusted sound fields and equalizer settings and displayed when they are selected.

DSP Functions

Turning the DSP effect on and off

Press the DSP button [5] for more than 2 seconds to turn the DSP effect on and off.
When the DSP effect is on, "DSP B1", "DSP B2" or "DSP U" appears on the display.

Fine-adjusting the listening position

1) Press the A-M button [12] to set the listening position adjustment display.
2) Press the ENT button [17] to select the position to be adjusted. The position switches as follows each time the ENT button is pressed:
   FULL SEAT → FRONT-R → FRONT-L → FRONT → REAR → PASS → FULL SEAT
3) Use the up and down buttons [15] to adjust the fader.
4) Use the right and left buttons [16] to adjust the balance.

Selecting the DSP sound field

1) Press the FUNC button [13] to select the desired mode.
2) Press the DSP button [5] so that "DSP" flashes on the display.
3) Press the BAND button [6] and select the group including the desired sound field.
   The group changes as follows each time the BAND button is pressed:
   DSP BASIC-1 → DSP BASIC-2 → DSP-USER → DSP BASIC-1
   (When the DPH7100 is connected, only "DSP BASIC" can be selected.)
4) Use the direct buttons [9] to select the desired sound field.

Sound fields

<DSP BASIC 1>

1. **HALL:** Sound of a large concert hall. (𝄞)
2. **CHURCH:** Sound of a church with a very high ceiling. (𝄞)
3. **STADIUM:** Sound of a large stadium with no ceiling or walls. (♪)
4. **LIVEHOUSE:** Sound of a live performance hall, somewhat larger than a jazz club. (♪)
5. **DISCO:** Sound of a disco with strong bass. (♪)

6. JAZZCLUB: Sound of a jazz club with a low ceiling. (♪)

<DSP BASIC 2>

1. DOME: Sound of an indoor sports arena. (𝄞)
2. CHAMBER: Sound of a large hall in a palace. (𝄞)
3. PARK: Sound of a spacious outdoor area. (♪)
4. THEATER: Sound of a movie or drama theatre. (♪)
5. STUDIO: Sound of a listening room in a home. (♪)
6. BGM: Sound with the vocals cut. (★)

* (𝄞) - Reverberation type sound fields
(♪) - Early reflection type sound fields
(★) - "BGM" (background music) type sound field

Editing DSP sound field settings

1) Select the preset sound field to serve as a base.
2) Press the DSP button [5] so that "DSP" flashes on the display.
3) Press the ADJ button [14].
4) Use the up and down buttons [15] to select "DSP EDIT", then press the ENT button [17].
5) Use the left and right buttons [16] to select the parameter to be adjusted.
6) Use the up and down buttons to adjust the setting.
7) To store a setting in the memory, press one of the direct buttons [9] for more than 2 seconds. (Only when the DPH9100 is connected)
8) Press the ADJ button.

Parameters which can be adjusted in the "DSP EDIT" mode

1. EFFECT: Percentage of reflected sound (0% ~ 100%)
2. INITIAL-DLY: Sense of distance between sound source and walls (1ms ~ 100ms)
3. REVERB TIME: Length of reverberations (0.3s ~ 10.0s)
4. ROOM SIZE: Sense of expansion (0.1 ~ 4.0)
5. HIGH: Percentage of high frequencies in reverberations (0.1 ~ 4.0)
6. LIVENESS: Sense of dynamism (0 ~ 10)

* For details on the parameters, refer to the DSP unit's operating instructions.

* When the DPH7100 is connected, only the "EFFECT" parameter can be edited.

* For some sound fields, not all the parameters can be adjusted.

For reverberation type sound fields (𝄞): The "ROOM SIZE" and "LIVENESS" parameters cannot be adjusted.

For early reflection type sound fields (♪): The "REVERB TIME" and "HIGH" parameters cannot be adjusted.

For the BGM type sound field (★): Only the "EFFECT" parameter can be adjusted.

Giving titles to DSP and equalizer settings (only when the DPH9100 is connected)

1) Press the DSP [5] or EQ [4] button so that "DSP" or "EQ" flashes on the display.
2) Press the BAND button [6] to select "DSP USER" or "EQ USER".
3) Use the direct buttons [9] to select the number of the user setting (U-1 to U-6) to which you want to give a title.
4) Press the ADJ button [14].
5) Use the up and down buttons to select "DSP TITLE" or "EQ TITLE", then press the ENT button [17].
6) Use the left and right buttons [16] to select the cursor position, then use the up and down buttons to select and input the characters.
   The characters change as follows each time the SHIFT button [8] is pressed:
   Capital letters → Numbers → Umlaut and accented letters → Small letters → Symbols → Capital letters
   * Up to 11 characters can be set.
7) Press the ENT button for more than 2 seconds to store the title in the memory.
8) Press the ADJ button.

Turning the auto loudness function on and off (only when the DPH9100 is connected)

Press the LD button [12] for more than 2 seconds. "A.LD" appears on the display, and the auto loudness function is turned on.
Press the LD button again for more than 2 seconds to turn the auto loudness function off.

Adjusting the auto loudness function

The amount of compression can be adjusted (between 0 ~ 10) without changing the loudness.

1) Press the DSP button [5] so that "DSP" flashes on the display.
2) Press the ADJ button [14].
3) Use the up and down buttons [15] to select "A.LD ADJ", then press the ENT button [17].
4) Use the up and down buttons to adjust the setting.
5) Press the ADJ button.

Equalizer Functions

Turning the equalizer effect on and off

Press the EQ button [4] for more than 2 seconds to turn the equalizer effect on and off.
When the equalizer effect is on, "EQ B" or "EQ U" appears on the display.

Selecting the equalizer setting

1) Press the FUNC button [13] to select the desired mode.
2) Press the EQ button [4] so that "EQ" flashes on the display.
3) Press the BAND button [6] and select the group including the desired sound field.
   The group changes as follows each time the BAND button is pressed:
   EQ BASIC → EQ USER → EQ BASIC
4) Use the direct buttons [9] to select the desired equalizer setting.

<Equalizer settings>

1. BASS BOOST: Low frequencies emphasized.
2. HIGH BOOST: Medium and high frequencies emphasized.
3. ACOUSTICAL: Medium frequencies (vocals) emphasized.
4. IMPACT: Low and high frequencies emphasized.
5. SMOOTH: Soft, relaxed sound.
6. FLAT: The original sound.

Editing the equalizer settings

1) Select the preset equalizer setting to serve as a base.
2) Press the EQ button [4] so that "EQ" flashes on the display.
3) Press the ADJ button [14].
4) Use the up and down buttons [15] to select the desired adjustment, then press the ENT button [14].
5) When "EQ EDIT", "EQ MIN FREQ", "SUB WOOFER" or "P.EQ" has been selected, use the left and right buttons [16] to select the parameter to be adjusted.

*The "P.EQ" parameter can only be adjusted when the DPH9100 is connected.

6) Use the up and down buttons to adjust the setting.
7) To store a setting in the memory, press one of the direct buttons [9] for more than 2 seconds.
8) Press the ADJ button.

* For details on the parameters, refer to the equalizer's operating instructions.

Equalizer adjustments

<EQ EDIT>

Use this to adjust the levels of the various frequencies.
If the SHIFT button [8] is pressed while in the equalizer editing mode, the equalizer curve appears, so you can adjust the settings while looking at the curve. Press the DISP button again to return to the previous display.

<EQ MIN FREQ (when the DPH9100 or DPH7100 is connected)>

This function allows you to switch the minimum adjustment frequency between 30Hz and 50Hz.

<Parameters which can be adjusted in the "SUB WOOFER" mode>

1. STEREO/MONO: Switch this according to the number of speakers being used. (off ~ MONO ~ STEREO)
2. WOOFER VOL: Sets the woofer's volume. (0 ~ 14)
3. LPF: Sets the low-pass filter's frequency. (50Hz ~ 80Hz ~ 120Hz)
4. LPF SLOPE: Sets the low-pass filter's slope. (12dB/oct ~ 18dB/oct ~ 24dB/oct)
5. HPF: Sets the high-pass filter's frequency. (Through ~ 50Hz ~ 80Hz ~ 120Hz)
6. HPF SLOPE: Sets the high-pass filter's slope. (12dB/oct ~ 18dB/oct ~ 24dB/oct)
7. TEST TONE: Used for testing the speaker wiring.

* When the "STEREO/MONO" setting is turned off, parameters 2, 3 and 4, and parameter 7 "WOOFER-L" and "WOOFER-R" cannot be adjusted.

* Parameters 4 and 6 can only be adjusted when the DPH9100 is connected.

* Parameter 7 cannot be adjusted when the EQH5100 is connected.

<Parameters which can be adjusted in the "P.EQ" mode (only when the DPH9100 is connected)>

1. P.EQ F/R: Switches between the front and rear. (off ~ REAR ~ FRONT)
2. F PRESET: Selects one of 6 types of parameters according to car type. (TYPE 1 ~ TYPE 6)

3. **R PRESET**: Selects one of 7 types of parameters according to car type. (TYPE 1 ~ TYPE 7)
4. **BAND**: Selects the band to be adjusted. (1 ~ 4: 1 and 2 are for low frequencies, 3 and 4 for medium and high frequencies)
5. **FREQUENCY**: Selects the centre frequency for the adjustment. (1 and 2: 20Hz to 500Hz, 3 and 4: 630Hz to 20kHz)
6. **GAIN**: Adjusts the level. (-12dB ~ +12dB)
7. **Q**: Adjusts the sharpness of the frequency curve. (1, 3, 5, 7 and 20)

* Parameters 2 to 7 cannot be adjusted when the "P.EQ F/R" parameter is turned off.

* If the SHIFT button [8] is pressed while in the parametric equalizer adjustment mode, the parametric equalizer curve appears, so you can adjust the settings while looking at the curve. Press the DISP button again to return to the previous display.

<PINK NOISE>

Pink noise (adjustment sounds) can be emitted in the order shown below by pressing the SHIFT button [8] for more than two seconds while in the parametric equalizer adjustment mode.

Front ➜ Rear ➜ All ➜ Off ➜ Front

<SURROUND (only when the EQH5100 is connected)>

The surround effect can be turned on and off.

* For details on the adjustment items, see the DSP or equalizer manual.

NOTES:

When the DSP979E or 900SEQ is connected, the corresponding mode must be set.

<Setting the DSP mode>

1. Set the DSP unit's volume to the minimum and the ARX9170R's volume to the maximum.
2. Press direct button [9] number "2" while holding in the SHIFT button [8]. "DSP connect" appears on the display, and the DSP mode is set.
3. To cancel the DSP mode, once again press direct button [9] number "2" while holding in the SHIFT button [8]. "DSP no conn" appears on the display, and the DSP mode is canceled.

<Setting the equalizer mode>

1. Press direct button [9] number "3" while holding in the SHIFT button [8]. "EQ connect" appears on the display, and the equalizer mode is set.
2. To cancel the equalizer mode, once again press direct button [9] number "3" while holding in the SHIFT button [8]. "EQ no conn" appears on the display, and the equalizer mode is canceled.

* For operations, refer to the DSP or equalizer's owner's guide.

7. TROUBLESHOOTING

Problem	Cause	Solution
Power does not turn on. (No sound is produced.)	Fuse is blown.	Replace with a fuse of the same amperage. If the fuse blows again, consult your store of purchase.
	Incorrect wiring.	Check the connections again and connect properly.
Sound quality is poor.	Playback head is dirty.	Use a cleaning tape, etc., to clean the head.
	DOLBY NR button is not pressed.	When listening to a tape recorded with Dolby NR, press the DOLBY NR button and select B NR or C NR.
Nothing happens when buttons are pressed.	Microprocessor has malfunctioned due to noise, etc.	Turn off the power, then press the release button and remove the front panel. Release button  Press the reset button for about 2 seconds with a thin rod, etc. 
	DCP or Main Unit connectors are dirty.	Wipe the dirt off with a soft cloth moistured in alcohol.
DSP or equalizer does not operate.	Microprocessor has malfunctioned due to noise, etc.	Press direct button 1 (for more than 2 seconds) while holding in the DSP button, then turn the power back on.

7. ERROR DISPLAYS

If an error occurs, the type of error is displayed. Take the measures described below to eliminate the problem.

Error display	Cause	Measure
TAPE ERROR8	Displayed when tape is caught and cannot be ejected.	Eliminate the reason for which the tape is caught.
CDAC ERRHHH	Displayed when the CD changer's internal temperature is too high and playback is stopped automatically.	Lower the surrounding temperature and wait a while for the CD changer's temperature to decrease.
CDAC ERROR3	Displayed when disc cannot be played due to scratches, etc.	Replace with a non-scratched, non-warped disc.
CDAC ERROR6	Displayed when disc cannot be played because it is loaded upside-down.	Eject the disc, then reload it properly.
MD ERROR3	Displayed when MD cannot be played due to scratches, etc.	Replace with a non-scratched disc.
EQ ERROR99	Communication error between main unit and DSP unit.	Turn the power on and off repeatedly.

If an error display other than the ones described above appears, press the reset button. If the problem persists, turn off the power and consult your store of purchase.

8. SPECIFICATIONS

Radio Section

Tuning System.....PLL synthesizer tuner
Receiving Frequencies.....
FM: 87.5 to 108 MHz (0.05 MHz steps)
MW: 531 to 1,602 kHz (9 kHz steps)
LW: 153 to 279 kHz (1 kHz steps)

Tape Deck Section

Cassette Type.....Compact Audio Cassette
Playback System
.....Auto reversing 4-track, 2-channel stereo cassette tape playback (monaural playback also possible)
Tape Types.....Metal, Chrome, Normal

General

Power Supply Voltage
.....DC 14 V (10.8 to 15.6 V allowable), negative ground
Power Consumption.....Less than 3 A
Auto Antenna Rated Current
..... 350 mA or less
Weight.....1.6 kg
Dimensions.....178 (W) x 50 (H) x 152 (D) mm



Note:

- Short-circuiting the power antenna terminal or using a power antenna with a current exceeding the rated current can damage internal circuits. Always use with the rated current.
- Specifications and design are subject to change without notice for further improvement.